

ANTI RUST PG 15

Product code: 265202401

Anti-corrosive anti shock

This product is a solid product of plastic consistency at room temperature. Once melted, it forms a thick and elastic film on the parts of easy elimination. This anticorrosive film provides in addition great resistance to impact and abrasion.

Applications

The product is suitable for the protection of such as screws, valves, gears, bearings, tools, segments, car spares and machines, cutlery and springs.

Benefits & Advantages

- Good protection against all kind of rust
- Easy application
- Protects from impacts and abrasion
- Easy to remove
- Safe and economic in use
- Non-toxic and risk-free under normal conditions of use
- Can be re-used

Typical Performance Data

Typical	Value
Film type	Plastic, elastic, peel off
Color	Light yellow, transparent
Temperature of use, °C	130-180
Spread power, approx., m2/kg	1,8-3
Anti-rust power	Limitless
Removal	Peeling off
Film thickness, mm	1-2,4

All performance data on this Technical Data Sheet are indicative only and can vary during production.

Method of use

This product is always applied in hot, by immersion of the parts to protect in the bath that contains the melted product. Smaller films are to be applied at maximum temperature and vice versa to obtain a thicker film. It is not recommended to use temperatures above 180 °C, because of the possible decomposition of the film. It is recommended to use FUSION TANK model T-1, regulated by thermostat. The temperature of the melting tank should not be increased too fast.