

HYDROMAX AW 32

Product code: 261300801

Mineral based high performance hydraulic fluid

High performance hydraulic fluid, based on the latest base oil and additive technology. The use of an ashless additive pack warrants optimal performance and a long service life.

It can be used in all available hydraulic applications, as well as light gear boxes and is perfectly suitable for general lubrication purposes.

Benefits & Advantages

- Excellent anti wear protection
- Good emulsifying and air-release properties
- Good anti oxidation for a long service life
- Excellent anti corrosion properties

Specifications

It is formulated to meet and exceed;

- Vickers I-286-S & M-2950-S
- AFNOR NF E 48-603 HM
- DIN 51 524 PART 2 (HLP)
- VDMA 24318
- US STEEL 126/127
- Thyssen TH-N-256132
- FZG A/8.3/90 > 12 (ISO VG 46 and higher)
- FZG A/8.3/90 = 12 (ISO VG 15, 22 and 32)
- CINCINATTI MILACRON P68/P69/P70 (ISO VG 32-68)

Typical Performance Data

Typical	Test Method	Value
Density @ 15 °C kg/m ³ 0.880		871
Viscosity 40 °C, cSt 68		32
Viscosity 100 °C, cSt 8.7		5.4
Viscosity index 95		98
Flash point C.O.C., °C 220		180
Pour point, °C -24		-27
Air Release Value @ 50°C		Pass
Demulsibility @54°C		Pass

All performance data on this Technical Data Sheet are indicative only and can vary during production.